

Model	=Electric	BT30ERT	BT28ERT	BT26SERT	BT26ERT	BT24ERT	BA28ERT	BA24ERT
	=Engine	BT30RT	BT28RT	BT26SRT	BT26RT	BT24RT	BA28RT	BA24RT
Type	Telescopic Boom Lifts						Articulating Boom Lifts	
Size								
Max. Working Height		30.30m	28.60m	26.70m	26.32m	24.80m	28.10m	24.30m
Max. Platform Height		28.30m	26.60m	24.70m	24.32m	22.80m	26.10m	22.30m
Max. Horizontal Reach		22.70m	21.30m	19.20m	19.47m	17.30m	18.80m	16.50m
Overall Length(Stowed) A		12.25m	11.66m	10.83m	10.82m	10.25m	11.83m	9.83m
Overall Length(Transport)		11.96m	11.82m	11.12m	10.77m	10.81m	12.03m	10.03m
Overall Width(Stowed) B		2.50m						
Overall Width(Transport)		2.31m						
Overall Height(Stowed) C		2.89m						
Overall Height(Transport)		2.57m						
Platform Size(Length×Width)		2.44m×0.9m						
Turntable Tailswing		1.61m						
Ground Clearance D		0.41m						
Wheelbase E		2.8m						
Turning Radius(Inside/Outside)		1.87m/3.22m						
Tyres		385/45-28						
Up And Over Clearance								9.14m
Max. Down Probing Depth							6.61m	4.03m
Performance								
S.W.L(Unrestricted/Restricted)		300kg/454kg	454kg				250kg	300kg
Max. Occupants		3						2
Gradeability		30% 45%	30% 45%	30% 45%	30% 45%	30% 45%	30% 45%	30% 45%
Travel Speed(Stowed)		6km/h						
Travel Speed(Raised)		1.1km/h						
Max. Working Slope		X-5°/Y-5°						
Turret Rotation		360° Continuous						
Platform Rotation		180°						
Jib Movement		130°						
Weight								
Overall Weight		18800kg	18300kg	16500kg	15990kg	14200kg	18300kg	17100kg
Power								
Power Source		Lithium Battery 520Ah/80V Charger 5kW/80V,12V			Diesel Engine Deutz TD2.9 L4 55.4kW			
Hydraulic Oil Tank		150L						

