



ELECTRIC SCISSOR LIFT

AS0607 / AS0607W

(AS1930 / AS1932)

HIGHLIGHTS

LGMG hydraulic motor drive scissor lifts offer industry leading reliability and simple design. They can be applied to various construction sites, maintenance job sites and other applications, both indoor and outdoor. The wide range product line from 5.8m to 13.8m platform height make these machines suitable for a wide range of requirements.


- Upgraded and reinforced design delivers better performance for various harsh conditions.
- The simple and reliable hydraulic system offers better productivity performance.
- Swing out component trays for easy access and maintenance.
- CAN bus system and intelligent self-diagnostic system for quick troubleshooting.
- Commonality in key parts with other scissor lifts.



LGMG Hydraulic Motor Drive Scissor Lift

SPECIFICATIONS

MODELS	AS0607 (AS1930)		AS0607W (AS1932)	
Measurements	Metric	US	Metric	US
Working Height Max.	7.8m	25.6ft	7.8m	25.6ft
A Platform Height-Raised	5.8m	19ft	5.8m	19ft
B Platform Height-Stowed	1.02m	3.3ft	1.02m	3.3ft
C Platform Length	1.63m	5.3ft	1.63m	5.3ft
D Platform Width	0.74m	2.4ft	0.74m	2.4ft
E Overall Length(with ladder)	1.83m	6ft	1.83m	6ft
F Overall Width	0.76m	2.5ft	0.81m	2.7ft
G Overall Height-Rails Up	2.12m	7ft	2.12m	7ft
Overall Height-Rails Down	1.82m	6ft	1.82m	6ft
H Extension Deck	0.9m	3ft	0.9m	3ft
I Wheelbase	1.32m	52in	1.32m	52in
Ground Clearance(Stowed/Raised)	60/20mm	2.36/0.79in	60/20mm	2.36/0.79in
PRODUCTIVITY				
Platform Occupants Max. (in/out)	2/0	2/0	2/1	2/1
Platform Capacity	230kg	510lbs	230kg	510lbs
Platform Capacity-Extension	120kg	265lbs	120kg	265lbs
Drive Height	Full Height			
Gradeability-Stowed	25 %			
Turning Radius-Inside	0			
Turning Radius-Outside	1.65m	5.4ft	1.65m	5.4ft
Raise/Lower Speed	16/28s		16/28s	
Brakes	Rear-wheel Brake			
Drive Mode	4×2			
Tires Type	Solid Non-marking			
Tires Size	305×114mm	12×4.5in	305×114mm	12×4.5in
POWER				
Power Source	24V DC 225Ah			
HYDRAULIC SYSTEM				
Hydraulic Oil Capacity	9.5L	2.1gal	9.5L	2.1gal
WEIGHT				
Machine Weight(CE/ANSI)	1580kg	3483lbs	1600kg	3527lbs



STANDARD FEATURES

- Proportional control
- Foldable guardrail
- Emergency stop device
- Manual brake release
- Emergency descent
- Swing-out component tray
- Pothole guard
- Self-lock entry gate
- Tilt alarm with lift cut-out
- Overload sensing system
- Descent alarm with flashing beacon
- Horn/Hour meter
- All motions alarm
- Full-height drive
- Intelligent diagnostic system

OPTIONAL

- AC power to platform
- Platform anti-collision device
- Air tube to platform
- Maintenance-free battery
- Lithium battery
- GPS

Machines in compliant with EN280 / ANSI 92.20 Standard.

Specifications subject to change without notice. Photos and diagrams in the page are for promotional purposes only.
2020 V1 Version

LINGONG GROUP JINAN HEAVY MACHINERY CO., LTD.

Address: No. 2676, Kejia Road, Jinan, Shandong, China
Email: sales@lgmg.com.cn Tel: +86-0531-67879283

LGMG Europe B.V.

Address: Laanweg 16 3208LC Spijkenisse Rotterdam, The Netherlands

LGMG North America, Inc.

Address: 1445 Sheffler Dr, Chambersburg, PA. 17201, USA



RELIABILITY IN ACTION