

TELESCOPIC BOOM LIFT T20J(T65J) / T26J(T85J)



HIGHLIGHTS

LGMG T Series telescopic boom lifts offer great outreach with high working efficiency. Its exceptional all terrain capacities allow the machine to operate on the roughest ground and complete the tasks on time.

- Oscillating axels and four-wheel drive delivers better gradeability on rough terrain.
- Proportional control ensures smooth driving, precise positioning and comfortable operation.
- Continuous 360° rotation expands the operational area and makes operations more convenient.
- Swing out engine tray for easy access and maintenance.
- Intelligent self-diagnostic system for quick troubleshooting.

SPECIFICATIONS

| MODELS | T20J (T65J) | | T26J (T85J) | |
|---------------------------------|-----------------------------|----------|------------------------------|------------|
| Measurements | Metric | US | Metric | US |
| Working Height Max. | 21.7m | 71.2ft | 27.9m | 91.5ft |
| Platform Height | 19.7m | 64.6ft | 25.9m | 84.9ft |
| Horizontal Outreach | 17.2m | 56.4ft | 23.32m | 76.5ft |
| Below Ground Reach | 2.72m | 8.92ft | 2.89m | 9.48ft |
| Platform Length | 1.83m | 72in | 2.44m | 96in |
| Platform Width | 0.76m | 30in | 0.91m | 36in |
| Platform Capacity | 250kg | 551lbs | 250/340kg | 551/750lbs |
| Ⓐ Stowed Length | 9.47m | 31.07ft | 12.6m | 41.3ft |
| Ⓑ Overall Width | 2.495m | 8.186ft | 2.5m | 8.2ft |
| Ⓒ Stowed Height | 2.77m | 9.09ft | 2.86m | 9.38ft |
| Ⓓ Wheelbase | 2.51m | 8.24ft | 2.85m | 9.35ft |
| Ⓔ Ground Clearance | 0.395m | 1.296ft | 0.44m | 1.44ft |
| PRODUCTIVITY | | | | |
| Platform Occupants Max.(in/out) | 2/2 | 2/2 | 2/2 | 2/2 |
| Turntable Rotation | 360°Continuous | | 360°Continuous | |
| Turntable Tailswing | 1.22m | 4ft | 1.42m | 4.66ft |
| Drive Speed-Stowed | 4.8km/h | 3mph | 4.8km/h | 3mph |
| Drive Speed-Raised | 0.8km/h | 0.5mph | 0.8km/h | 0.5mph |
| Gradeability | 45% | | 45% | |
| Max. Wind Speed | 12.5m/s | 28mph | 12.5m/s | 28mph |
| Turning Radius-Inside | 2.5m | 8.2ft | 3.66m | 12ft |
| Turning Radius-Outside | 5.5m | 18ft | 6.55m | 21.5ft |
| Max.Slope | 2.5/4.5° | | 2.5/4.5° | |
| Tire type | RT Foam-filled | | RT Foam-filled | |
| Tires | 355/55D 625 | | 18-625 | |
| POWER | | | | |
| power source | Deutz D 2.9L4 36.4kw/48.8hp | | Deutz TD 2.9L4 55.4kw/74.3hp | |
| Fuel Tank Capacity | 100L | 26.4gal | 100L | 26.4gal |
| HYDRAULIC SYSTEM | | | | |
| Hydraulic Oil Capacity | 180L | 47.5gal | 180L | 47.5gal |
| WEIGHT | | | | |
| Machine Weight(CE/ANSI) | 11400kg | 25132lbs | 18000kg | 39683lbs |

